



MODULE	A	B	WATT	R1	R2	X	R
Small	605	38 (46 if assembled)	10, 14 ou 27	555	605	500	545
Medium	750		18, 27 ou 35	654	750	650	690
Large	1186		21, 27 ou 42	1090	1186	900	1095
XLarge	1484		34, 50 ou 69	1390	1486	1200	1395



Nom	W	CRI	K	Driver	Optic	Finition	Module	Inter-connexion
PROCYON	10 ¹	80CRI	2700K	Ecg-fix	Opal	White	Small	Single Direct 1 side ^{1,2} Direct 2 sides ^{3,4}
	14 ¹		3000K	DALI			Medium	
	18 ²		4000K	Wireless			Large	
	21 ^{1,3}		5700K				XLarge	
	27 ^{2,3}		6500K					
	34 ⁴							
	35 ²							
	42 ²							
	50 ⁴							
69 ⁴								

¹only small / ²only medium / ³only large / ⁴only Xlarge

Code ordering example: **PR02783DGOL2**

Finition:



PROCYON

Montage: Chemin lumineux et réglettes
Optique : Opal
Équipement électrique: Ballast électronique
 FIX/DALI (ECG/EDA)
Matériels: Aluminium
Durée de vie utile: 80000 heures L80/B50

Montage: Lichtbandleuchten und Lichtleisten
Optic : Opal
Vorschaltgerät: Elektronisches Vorschalt-
 gerät FIX/DALI (ECG/EDA)
Material: Aluminium
Lebensdauer: 80000 Stunden L80/B50

Mounting: Continuous line and batten
Optic : Opal
Wiring: Electronic control gear FIX/DALI
 (ECG/EDA)
Materials: Aluminium
Service lifetime: 80000 hours L80/B50

