


SPAMP



LED

220
240 V
50-60 Hz

SDCM
3

DIMM

IP
20

CRI
80

MULTI


EN
62 471
RG 0

80 000
L80B50


η_{ef} (lm/W)
95-115



SPAMP190



SPAMP KN



SPAMP KO











Surface round fittings

Body:
White painted (RAL 9003) metal sheet

Optic:
Translucent acrylic layer with a cover
KN - microprismatic cover
KO - opal cover

SPAMP	W	lm		C	Ø	X	Y	kg	
		KO	KN						
SPAMP1000 190	9	970	1 050	56	184	120	140	0,9	
SPAMP1500 190	13	1 350	1 450						
SPAMP2000 190	19	1 800	1 950						
SPAMP3000 370	26	2 800	3 000		365	200	230		2,0
SPAMP3000 370 MULTI	20 - 29	2100 - 3100	2 200 - 3 200						
SPAMP4000 370	34	3 550	3 800						
SPAMP4000 550	34	3 650	3 800		548	400	400		3,0
SPAMP5000 550	40	4 100	4 500						

lm - luminaire light output

2200	2700	3000	4000	5700	6500	MIX	RGB	
✗	○	○	●	○	✗	✗	✗	✗
								
●	✗	○	○	✗	✗	✗	✗	✗

● default ○ optional ✗ not possible

